

# LUBRICANTS FOR IVECO COMMERCIAL VEHICLES



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for IVECO.

Product	Description	Specifications	Approvals	FUCHS Recommendations
<b>Engine Oils</b>				
<b>TITAN</b> <b>CARGO MAXX</b> <b>SAE 5W-30</b>  	Premium MAXX Performance Engine Oil with new XTL®-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Optimum cold starting properties and ageing stability for extreme fuel-economy over the whole drain-interval.	ACEA E9/E7/E6/E4 API CJ-4	–	IVECO 18-1804 CLASSE TLS E6
<b>TITAN</b> <b>CARGO MAXX</b> <b>SAE 10W-40</b>  	Premium MAXX Performance Engine Oil with new XTL®-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Good cold starting properties and ageing stability for fuel-economy over the whole drain-interval.	ACEA E9/E7/E6/E4 API CJ-4	–	IVECO 18-1804 CLASSE TLS E9 IVECO 18-1809 CLASSE NG2
<b>TITAN</b> <b>CARGO SL</b> <b>SAE 5W-30</b>	Ultra High Performance, extreme fuel-economy engine oil for a variety of commercial vehicle diesel engines, with optimum cold starting and lower oil consumption. Specially developed for extended service intervals.	ACEA E7/E4	–	IVECO 18-1804 CLASSE TFE
<b>TITAN</b> <b>CARGO MC</b> <b>SAE 10W-40</b>	Ultra High Performance, fuel-economy engine oil based on MC-synthesis for a variety of commercial vehicle diesel engines. Specially developed for extended service intervals. Good cold starting and lower oil consumption.	ACEA E7/E4 API CI-4	–	IVECO 18-1804
<b>TITAN</b> <b>TRUCK PLUS</b> <b>SAE 15W-40</b>	Super High Performance Engine Oil for a variety of diesel and gasoline engines. Specially for highly-loaded commercial vehicle diesel engines. Lower oil consumption.	ACEA E7 API CI-4/SL	–	IVECO 18-1804 CLASSE T2 E7
<b>Gear Oils</b>				
<b>TITAN</b> <b>CYTRAC ULTRA</b> <b>SYNTH</b> <b>SAE 75W-80</b>	Premium Performance Gear Oil for gear boxes in commercial vehicles, especially developed for ZF heavy duty transmissions with and without Intarder. Reduces fuel consumption by improving gearbox efficiency. Suitable for longest oil change intervals.	API GL-4 ZF TE-ML 01E, 02E, 16P (ZF001457)	–	–
<b>TITAN</b> <b>CYTRAC MAN SYNTH</b> <b>SAE 75W-80</b>	Premium Performance Gear Oil for gear boxes in commercial vehicles, specially developed for manual and automatic ZF-gear boxes, formulated with fully-synthetic base oils. Reduces fuel consumption by improving gearbox efficiency. Suitable for the longest oil change intervals and compatible with Carbon-Synchronizers.	API GL-4 ZF TE-ML 01L, 02L, 16K (ZF001140)	–	–
<b>TITAN</b> <b>SUPERGEAR MC</b> <b>SAE 80W-90</b>	Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5 ZF TE-ML 02B, 05A, 12L, 12M, 16B, 17B, 19B, 21A (ZF000722)	–	–
<b>TITAN</b> <b>CYTRAC SL</b> <b>SAE 75W-90</b>	Premium Performance Gear Oil for highly-stressed hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals in commercial vehicle axle drives.	API GL-5	–	–
<b>TITAN</b> <b>CYTRAC HSY</b> <b>SAE 75W-90</b>	Ultra High Performance Gear Oil for commercial vehicle manual transmissions and axle drives formulated with fully-synthetic base oils.	API GL-4/GL-5	–	–
<b>TITAN</b> <b>CYTRAC HYP LD</b> <b>SAE 80W-90</b>	Super High Performance Gear Oil specially developed for Mercedes-Benz commercial vehicles. Offering enhanced thermal stability and fuel-economy potential.	API GL-5 API MT-1 SAE J2360	–	–

Product	Description	Specifications	Approvals	FUCHS Recommendations
<b>Automatic Transmission Fluids (ATF)</b>				
<b>TTAN ATF 5005</b>	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: red.	ZF TE-ML 04D, 14B, 16L, 17C (ZF000717)	–	DEXRON III (H)
<b>TTAN ATF 3000</b>	Super High Performance DEXRON II (D) ATF for automatic transmissions in commercial vehicles, machinery and passenger cars according to manufacturer's documentation. Product dyeing: red.	ZF TE-ML 04D, 14A (ZF000720)	–	DEXRON II (D)
<b>Central Hydraulic Fluid</b>				
<b>TTAN ZH LHM PLUS</b>	Ultra High Performance Central Hydraulic Oil specially for the use in IVECO vehicles. Product dyeing: green.	–	–	IVECO 18-1823
<b>Antifreeze</b>				
<b>MAINTAIN FRICOFIN LL</b>	Premium Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange.	ASTM D 3306 TYPE I BS 6580:2010 SAE J814	–	–
<b>MAINTAIN FRICOFIN HDD</b>	Ultra High Performance Engine Coolant concentrate based on monoethylene glycol. Free of amines and phosphates with low silicate technology. Product dyeing: yellow.	ASTM D 3306 TYPE I ASTM D 4985 ASTM D 6210 TYPE I-FF ASTM D 7583 AS/NZS 2008:2004 TYPE A BS 6580:2010 SAE J814	–	IVECO 18-1830
<b>MAINTAIN FRICOFIN</b>	Super High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: blue-green.	AFNOR NF R 15-601 TYPE 1 ASTM D 3306 TYPE I ASTM D 4985 BS 6580:2010 SAE J814; SAE J1034	–	–
<b>Fuel Additives</b>				
<b>MAINTAIN DIESEL EFFECT</b>	Super High Performance Fuel Additive improving Diesel fuel properties for singular as well as constant treatment.	–	–	–
<b>MAINTAIN WINTERFIT</b>	Super High Performance Diesel Fuel and Heating Oil Additive to prevent waxing and plugging at low temperatures.	–	–	–
<b>Greases</b>				
<b>RENOLIT LZR 000</b>	Semi-fluid grease for engine vehicle central lubrication systems. Gear grease for gearboxes in municipal machinery. Observe manufacturer's recommendations, -40 °C to +110 °C.	–	–	–
<b>RENOLIT LX-PEP 2</b>	Special grease based on lithium complex soaps for long-life applications. Good corrosion protection, thermally and mechanically stable, specially suitable for wheel bearings of cars and trucks, -30 °C to +150 °C.	–	–	–

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.

© FUCHS SCHMIERSTOFFE GMBH. All rights reserved. Edition 08/2016

## FUCHS SCHMIERSTOFFE GMBH

Export Division ▪ Friesenheimer Straße 19 ▪ 68169 Mannheim/Germany

Phone: 0621 3701-1703 ▪ Fax: 0621 3701-7719

E-Mail: [export@fuchs-schmierstoffe.de](mailto:export@fuchs-schmierstoffe.de) ▪ [www.fuchs.com/de/en](http://www.fuchs.com/de/en)