



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. Therefore MERCEDES-BENZ counts on lubricants and specialities of FUCHS.

PRODUCT	CHARACTERISTICS	SPECIFICATIONS/ APPROVALS
<b>Engine Oils</b>		
<b>TITAN GT1 PRO FLEX</b> <b>SAE 5W-30</b> 	Premium Performance, extreme fuel-economy engine oil with new XTL®-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals.	<b>ACEA C3</b> <b>API SN/SM</b> MB-APPROVAL 229.51 MB-APPROVAL 229.52
<b>TITAN GT1 PRO C-3</b> <b>SAE 5W-30</b> 	Premium Performance, extreme fuel-economy engine oil with new XTL®-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals.	<b>ACEA C3</b> MB-APPROVAL 229.51
<b>TITAN CARGO MAXX</b> <b>SAE 5W-30</b> 	Premium MAXX Performance Engine Oil with new XTL®-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Optimum cold starting properties and ageing stability for extreme fuel-economy over the whole drain-interval.	<b>ACEA E6</b> MB-APPROVAL 228.51
<b>TITAN GT1</b> <b>SAE 5W-40</b> 	Premium Performance, fuel-economy engine oil with new XTL®-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for vehicles with exhaust after treatment and turbocharger.	<b>ACEA C3</b> <b>API SN/SM/CF</b> MB-APPROVAL 226.5 MB-APPROVAL 229.31
<b>TITAN GT1 PRO B-Tec</b> <b>SAE 5W-30</b> 	Premium Performance, extreme fuel-economy engine oil with new XTL®-Technology for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially for Mercedes-Diesel-Vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions.	<b>ACEA C2/C3</b> <b>API SN</b> MB-APPROVAL 229.52
<b>TITAN Supersyn</b> <b>SAE 5W-40</b>	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	<b>ACEA A3/B4</b> <b>API SN/SM/CF</b> MB-APPROVAL 229.3
<b>Gear Oils</b>		
<b>TITAN SINTOFLUID</b> <b>SAE 75W-80</b>	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	<b>API GL-5</b>
<b>TITAN GEAR MP</b> <b>SAE 80</b>	High Performance Gear Oil for synchronized and non-synchronized manual gearboxes as well as auxiliary drives, axles and differentials in commercial vehicles and passenger cars.	<b>API GL-4</b> MB-APPROVAL 235.1
<b>TITAN SINTOPOID FE</b> <b>SAE 75W-85</b>	Premium Performance Gear Oil offering increased gearbox efficiency in passenger cars due to low viscosity level, formulated with fully-synthetic base oils. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	<b>API GL-5</b> MB-APPROVAL 235.7 ZF TE-ML 18
<b>TITAN CYTRAC 235.8</b> <b>SAE 75W-90</b>	Premium Performance Gear Oil for highly-stressed hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals especially in DAIMLER commercial vehicle axle drives.	<b>API GL-4/GL-5</b> MB-APPROVAL 235.8
<b>TITAN CYTRAC SL</b> <b>SAE 75W-90</b>	Premium Performance Gear Oil for highly-stressed hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals in commercial vehicle axle drives.	<b>API GL-5</b>
<b>TITAN SUPERGEAR MC</b> <b>SAE 80W-90</b>	Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	<b>API GL-4/GL-5</b> MB-APPROVAL 235.0

PRODUCT	CHARACTERISTICS	SPECIFICATIONS/ APPROVALS
<b>Automatic Transmission Fluids (ATF)</b>		
<b>TITAN ATF 7134 FE</b>	Premium Performance ATF with reduced viscosity, especially developed to further optimize fuel-economy and gearbox efficiency of latest generation Mercedes-Benz 7-speed automatic transmissions. Not downwards compatible with previous MB-ATF-Specifications. Product dyeing: blue.	MB-APPROVAL 236.15
<b>TITAN ATF 5005</b>	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: red.	MB-APPROVAL 236.6
<b>TITAN ATF 4134</b>	Ultra High Performance ATF, specially developed to optimise shifting performance of Mercedes automatic transmissions. Product dyeing: red.	MB-APPROVAL 236.14
<b>TITAN ATF 4000</b>	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	MB-APPROVAL 236.1 MB-APPROVAL 236.9
<b>TITAN ATF 3353</b>	Ultra High Performance DEXRON III-generation-ATF for automatic transmissions as well as any other ATF-applications. Developed for the MB automatic transmissions and transfer cases according manufacturer. Offers fuel-efficiency potential. Product dyeing: red.	MB-APPROVAL 236.12
<b>TITAN ATF CVT</b>	Ultra High Performance ATF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none.	MB-APPROVAL 236.20
<b>Central Hydraulic / Power Steering Fluids</b>		
<b>TITAN ZH 4300 B</b>	Premium Performance Central Hydraulic Oil formulated with fully-synthetic base oils. Product dyeing: green.	
<b>TITAN ZH 5364 B</b>	Premium Performance Central Hydraulic Oil approved by Mercedes-Benz for level control systems in passenger cars formulated with fully-synthetic base oils. Product dyeing: none.	MB-APPROVAL 344.0
<b>TITAN PSF</b>	Super High Performance Power Steering Fluid approved by Mercedes-Benz for passenger cars and commercial vehicles. Product dyeing: none.	MB-APPROVAL 236.3
<b>Antifreeze</b>		
<b>MAINTAIN FRICOFIN LL</b>	Premium Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange.	MB-APPROVAL 325.3
<b>MAINTAIN FRICOFIN DP</b>	Ultra High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: pink - violet.	MB-APPROVAL 325.5 MB-APPROVAL 325.6
<b>MAINTAIN FRICOFIN</b>	Super High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: blue-green.	MB-APPROVAL 325.0
<b>Brake Fluid</b>		
<b>MAINTAIN DOT 4</b>	Super High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/DOT 4 ISO 4925 CLASS 3/4 SAE J 1703/J 1704

The information contained in this product information leaflet is based on the experience, knowledge and expertise of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state of the art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products are subject to continuous further development. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning. With publication of this product information leaflet, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.  
© FUCHS SCHMIERSTOFFE GMBH. All rights reserved. Version 11/2015

## FUCHS SCHMIERSTOFFE GMBH Export Division

Friesenheimer Straße 19 · 68169 Mannheim / Germany  
Phone: +49 621 3701-1703 · Fax: +49 621 3701-7719  
export@fuchs-schmierstoffe.de · www.fuchs-schmierstoffe.de

LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

