

LUBRICANTS.
TECHNOLOGY.
PEOPLE.



LUBRICANTS FOR **VOLVO** PASSENGER CARS

Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. Therefore VOLVO counts on lubricants and specialities of FUCHS.

PRODUCT	CHARACTERISTICS	SPECIFICATIONS/ APPROVALS	FUCHS RECOMMEN- DATIONS
Motor Oils			
TITAN GT1 PRO V SAE 0W-20 	Premium Performance Engine Oil with new XTL®-Technology in ground-breaking viscosity class. Specially designed for modern VOLVO vehicles, for extreme fuel-economy characteristics and reduced CO ₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves.	VOLVO VCC RBS0-2AE 0W-20	
TITAN Supersyn FE SAE 0W-30	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting properties and low oil consumption.	ACEA A5/B5 VOLVO VCC 95200377	
TITAN Supersyn LONGLIFE SAE 0W-30	Ultra High Performance, extreme fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting and lower oil consumption.	ACEA A3/B4	
TITAN Supersyn LONGLIFE SAE 5W-40	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4	
TITAN Supersyn F Eco-DT SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil especially suitable for Ford DuraTorq-Diesel engines. Optimum cold starting and lower oil consumption.	ACEA A5/B5 FORD M2C913-C FORD M2C913-D	ACEA A1/B1 FORD M2C913-B
Gear Oils			
TITAN SINTOFLUID FE SAE 75W	Premium Performance Manual Transmission Fluid offering increased gearbox efficiency in passenger cars due to low viscosity level. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-4	FORD M2C200-D2
TITAN SINTOFLUID SAE 75W-80	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5	API GL-4 FORD M2C200-C/ C2/ C3 VOLVO 97308/ 97309
TITAN SINTOPOID SAE 75W-90	Premium Performance Axle Gear Oil for passenger cars, also for high-offset hypoid drives offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5	VOLVO 97314
TITAN SINTOPOID FE SAE 75W-85	Premium Performance Gear Oil offering increased gearbox efficiency in passenger cars due to low viscosity level, formulated with fully-synthetic base oils. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-5	VOLVO 97314
TITAN SUPERGEAR MC SAE 80W-90	Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5	

PRODUCT	CHARACTERISTICS	SPECIFICATIONS / APPROVALS	FUCHS RECOMMENDATIONS
Double Clutch Transmission Fluids (DCTF)			
TITAN DCTF	Premium Performance DCTF, specially developed for modern Double Clutch Transmission with wet clutch. The wide performance profile offers the use in diverse Double Clutch Transmissions of different manufacturers. Provide optimum wear protection and excellent shifting properties even under hard conditions over the whole lifetime.		VOLVO-Powershift VOLVO 1161838
Automatic Transmission Fluids (ATF)			
TITAN ATF 4400	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.		DEXRON III JWS 3309
TITAN ATF 4000	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	DEXRON III (H)	
TITAN ATF 3000	Super High Performance DEXRON II (D) ATF for automatic transmissions in commercial vehicles, machinery and passenger cars according to manufacturer's documentation. Product dyeing: red.		DEXRON II (D)
Central Hydraulic / Power Steering Fluids			
TITAN ZH 3044	Ultra High Performance power steering and central Hydraulic Oil for automotive applications. Product dyeing: green.		ISO 7308 FORD M2C204-A2
TITAN ZH 4300 B	Premium Performance Central Hydraulic Oil formulated with fully-synthetic base oils. Product dyeing: green.		FORD M2C204-A
Antifreeze			
MAINTAIN FRICOFIN	Super High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: blue-green.		
Brake Fluids			
MAINTAIN DOT 4	Super High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/ DOT 4 ISO 4925 CLASS 3/4 SAE J 1703/J 1704	
MAINTAIN DOT 5.1	Ultra High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 5.1 ISO 4925 CLASS 3/4/5.1 SAE J 1703/J 1704	

The information contained in this product information leaflet is based on the experience, knowledge and expertise of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state of the art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products are subject to continuous further development. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning. With publication of this product information leaflet, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.

© FUCHS SCHMIERSTOFFE GMBH. All rights reserved. Version 05/2015

FUCHS SCHMIERSTOFFE GMBH Export Division

Friesenheimer Straße 19 · 68169 Mannheim / Germany
Phone: +49 621 3701-1703 · Fax: +49 621 3701-7719
export@fuchs-schmierstoffe.de · www.fuchs-schmierstoffe.de

PARTNER
DES DEUTSCHEN KRAFTFAHRZEUGEWERBES

LUBRICANTS.
TECHNOLOGY.
PEOPLE.

