




LUBRICANTS FOR KIA PASSENGER CARS



LUBRICANTS.
TECHNOLOGY.
PEOPLE.



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. Therefore KIA counts on lubricants and specialities of FUCHS.

PRODUCT	CHARACTERISTICS	SPECIFICATIONS
Motor Oils		
TITAN GT1 PRO FLEX SAE 5W-30 	Premium Performance, extreme fuel-economy engine oil with new XTL®-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for BMW, Mercedes-Benz and Opel vehicles with exhaust after treatment and turbocharger.	ACEA C3 API SN/SM
TITAN GT1 SAE 5W-40 	Premium Performance, fuel-economy engine oil with new XTL®-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for vehicles with exhaust after treatment and turbocharger.	ACEA C3 API SN/SM/CF
TITAN GT1 PRO B-Tec SAE 5W-30 	Premium Performance, extreme fuel-economy engine oil with new XTL®-Technology for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially for Mercedes-Diesel-Vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions.	ACEA C2/C3 API SN
TITAN Supersyn LONGLIFE SAE 0W-30	Ultra High Performance, extreme fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting and lower oil consumption.	ACEA A3/B4 API SL
TITAN Supersyn F Eco-B SAE 5W-20	Ultra High Performance, extreme fuel-economy engine oil especially developed for Ford EcoBoost gasoline engines. Optimum cold starting and lower oil consumption.	ACEA A1/B1 API SN
TITAN Supersyn F Eco-DT SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil especially suitable for Ford DuraTorq-Diesel engines. Optimum cold starting and lower oil consumption.	ACEA A1/B1 ACEA A5/B5 API SL/CF
TITAN Supersyn SAE 5W-40	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SN/SM/CF
TITAN SYN SN SAE 0W-20	Super High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Good cold starting behaviour and low oil consumption.	API SN ILSAC GF-5
Gear Oils		
TITAN SINTOFLUID SAE 75W-80	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5
TITAN SINTOPOID LS SAE 75W-90	Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/5/5 incl. LS
TITAN SUPERGEAR MC SAE 80W-90	Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5

PRODUCT	CHARACTERISTICS	SPECIFICATIONS/ FUCHS RECOM- MENDATIONS
Automatic Transmission Fluids (ATF)		
TITAN ATF 4400	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	ATF SP-III/IV DEXRON III PSF-III
TITAN ATF 3000	Super High Performance DEXRON II (D) ATF for automatic transmissions in commercial vehicles, machinery and passenger cars according to manufacturer's documentation. Product dyeing: red.	DEXRON II (D)
Power Steering Fluid		
TITAN ZH 3044	Ultra High Performance power steering and central Hydraulic Oil for automotive applications. Product dyeing: green.	PSF-IV
Antifreeze		
MAINTAIN FRICOFIN LL	Premium Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange.	ASTM D 3306 TYPE I BS 6580 ASTM D 4985 SAE J1034 JASO M325
MAINTAIN FRICOFIN	Super High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: blue-green.	AFNOR NF R 15-601 TYPE 1 ASTM D 3306 TYPE I ASTM D 4985 BS 6580:1992 SAE J1034
Brake fluids		
MAINTAIN DOT 5.1	Ultra High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 5.1 ISO 4925 CLASS 3/4/5.1 SAE J 1703/J 1704
MAINTAIN DOT 4	Super High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/ DOT 4 ISO 4925 CLASS 3/4 SAE J 1703/J 1704

The information contained in this product information leaflet is based on the experience, knowledge and expertise of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state of the art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products are subject to continuous further development. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning. With publication of this product information leaflet, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.
© FUCHS SCHMIERSTOFFE GMBH. All rights reserved. Version 09/2015

FUCHS SCHMIERSTOFFE GMBH
Export Division

Friesenheimer Straße 19 · 68169 Mannheim / Germany
Phone: +49 621 3701-1703 · Fax: +49 621 3701-7719
export@fuchs-schmierstoffe.de · www.fuchs-schmierstoffe.de

LUBRICANTS.
TECHNOLOGY.
PEOPLE.

